

RFI FILTER

Data Sheet

Datenblatt


Fiche Technique

FILTER TYPE
AX-FIM1010-RE

DIMENSIONS

ABMESSUNGEN


DIMENSIONS



CIRCUIT DIAGRAM

ELEKTR. SCHEMA

SCHEMA ELECTRIQUE



DATA	DATEN	CHARACTERISTIQUES	
RATED VOLTAGE	NENNSPANNUNG	TENSION NOMINALE	250V
RATED CURRENT	NENNSTROM	COURANT NOMINAL	10A
AT AMBIENT TEMP	BEI UMGEBUNGSTEMP	A UNE TEMPERATURE AMBIANTE	40°C
RATED OP FREQUENCY	BETRIEBSFREQUENZ	FREQUENCE DE SERVICE	48-62Hz
TEMPERATURE RANGE	ZULÄSSIGE BETRIEBSTEMP	GAMME DE TEMPERATURE	-25 -> +85°C
LEAKAGE CURRENT	ABLEITSTROM BEI -->E	COURANTE DE FUITE A	7mA
POWER LOSS	LEISTUNGSABFALL	PERTE DE PUISSANCE	
FLASH TEST VOLTAGE	PRÜFSPANNUNG	TENSION D'ESSAIS	2.2kVdc (P-E)
POTTING COMPOUND	VERGUSSMASSE	MATIERE DE MOULAGE	polyurethane
WEIGHT	GEWICHT	POIDS	0.6kg
APPROVALS	PRÜFZEICHEN	HOMOLOGATIONS	

ADDITIONAL INFORMATION
ZUSATZANGABEN
INFORMATIONS SUPPLEMENTAIRES

designed for use with Omron MX2 series 200V single phase inverters
AB001, AB002, AB004 (0.1 to 0.55kW)

9			
8			
7			
6			
5			
4			
3			
2			
1			
MODIFICATIONS	DATE	AUTHORISED	

FILTER TYPE	AX-FIM1010-RE
DRAWING No.	DS 101-FIM
ISSUE No.	0.2