





Power [kW] 0.27	Duty Cycle S1	Base speed [rpm] 18000	Base freq. [Hz] 300	Base voltage Δ [V] 220	Base voltage Y [V]	Protection IP54	Ins. Cl. F	 Teknomotor S.r.l. Via Argenega 31, I-32038 Quero Vas (BL) www.teknomotor.com
Min speed [rpm] 9000		Max speed [rpm] 24000	Max freq. [Hz] 400	Absorb. Δ [A] 1.4	Absorb. Y [A]	Part number on nameplate COM24310048		
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		tool type full key 	tool type half key 	Peso / weight 1.82 kg		
Tolleranze non quotate / unlisted tollerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	Title 2431-B-SB-P-ER11-RH
rev. n° 00	description Emissione			date 12/01/2017	signature D. Bottarel	Customer Catalogo		
						Drawing code COM24310048	Drawing n° 5040	
drawn - date E. Gaspari - 12/01/2017	approved - date S. Perli - 12/01/2017	checked - date S. Perli - 12/01/2017	sostituisce il sostituito dal		foglio / sheet 1 / 1	scala 1:2	 A4	