





Power [kW] 0.4	Duty Cycle S1	Base speed [rpm] 18000	Base freq. [Hz] 300	Base voltage Δ [V] 220	Absorb. Δ [A] 1.7	Base voltage Y [V]	Absorb. Y [A]	 Teknomotor S.r.l. Via Argenega 31, I-32038 Quero Vas (BL) www.teknomotor.com
Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]	
Min speed [rpm] 9000	Max speed [rpm] 24000	Max freq. [Hz] 400	Protection IP54	Ins. Cl. F	Part number on nameplate COM24310054			
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		cool type 	cool type 	Peso / weight 1.84 kg	Title 2431-C-SB-P-ER11-RR-RH	
rev. n° 00	description Emissione			date 30/04/2020	signature D. Bottarel	Customer Catalogo	Drawing code COM24310054	
						Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5 mm Rugosità secondo UNI ISO 1302		
drawn - date D. Bottarel - 30/04/2020	approved - date S. Perli - 30/04/2020	checked - date S. Perli - 30/04/2020	sostituisce il sostituito dal			folio / sheet 1 / 1	scala 1:2	 A4