



**ES WIRKT.**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name/designation Feinmechanik-Öl Ustanol-Spray  
Unique Formula Identifier UFI: 2DPJ-SEN8-700Q-JTAA

**\* 1.2 Relevant identified uses of the substance or mixture and uses advised against**

No data available

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer**

F.W.Klever  
Hauptstraße 20  
D-84168 Aham  
Telephone +49 (0) 8744 96 99 10  
Telefax + 49 (0) 8744 96 99 96  
E-mail info@ballistol.de  
Website www.ballistol.de

Department responsible for information:  
Qualitätssicherung  
Telephone +49 (0) 8744 96 99 80

E-mail (competent person):  
info@ballistol.de

**\* 1.4 Emergency telephone number**

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

**\* SECTION 2: Hazards identification**

**\* 2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]	Classification procedure
--	--------------------------

Aerosol 1, H222 H229  
Skin Irrit. 2, H315  
Aquatic Chronic 3, H412

**Hazard statements for physical hazards**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**Hazard statements for health hazards**

H315 Causes skin irritation.

**Hazard statements for environmental hazards**

H412 Harmful to aquatic life with long lasting effects.

**\* 2.2 Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Danger

**Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.  
P251 Do not pierce or burn, even after use.  
P211 Do not spray on an open flame or other ignition source.  
P210 From heat, hot surfaces, sparks, flames and other sources of ignition. Do not smoke.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container to recycling

**2.3 Other hazards**

No data available

**SECTION 3: Composition / information on ingredients**

**3.1 Substances**

not applicable

**3.2 Mixtures**

**Hazardous ingredients**

CAS No.	EC No.	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
74-98-6	200-827-9	propane	< 15 weight-%	Flam. Gas 1; H220 Press. Gas	
106-97-8	203-448-7	butane	< 15 weight-%	Flam. Gas 1; H220 Press. Gas	
		kurzkettige, aliphatische Kohlenwasserstoffe	< 15 weight-%	Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**Following inhalation**

Provide fresh air.  
In the event of symptoms refer for medical treatment.



**ES WIRKT.**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

**Following skin contact**

After contact with skin, wash immediately with plenty of water and soap.

**After eye contact**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**Following ingestion**

If swallowed, immediately drink:  
Water  
Seek medical advice immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor**

Treat symptomatically.

---

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Foam  
ABC-powder  
Carbon dioxide (CO<sub>2</sub>)  
Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products**

In the event of fire the following can be released:  
Nitrogen oxides (NO<sub>x</sub>)  
Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

**Special protective equipment for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers.  
Heating causes rise in pressure with risk of bursting  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Remove all sources of ignition.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
Special danger of slipping by leaking/spilling product.



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

**6.2 Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3 Methods and material for containment and cleaning up**

**For containment**

Take up residues with absorbent material (e.g. sawdust).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**6.4 Reference to other sections**

No data available

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

**Protective measures**

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Protect aerosols from temperatures exceeding 50°C/ 122°F

Do not inhale gases/vapours/aerosols.

**Advices on general occupational hygiene**

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep/Store only in original container.

**Storage class**

2B Aerosol dispensers and lighters

**Further information on storage conditions**

Recommended storage temperature: room temperature.

At appropriate storage unlimited stability.

**7.3 Specific end use(s)**

No data available

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

CAS No.	EC No.	Substance name	occupational exposure limit value
106-97-8	203-448-7	n-Butane	600 [ml/m <sup>3</sup> (ppm)] 1450 [mg/m <sup>3</sup> ] Short-term(ml/m <sup>3</sup> ) 750 Short-term(mg/m <sup>3</sup> ) 1810 (UK)



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

CAS No.	EC No.	Substance name	occupational exposure limit value
106-97-8	203-448-7	n-Butane	Short-term(ml/m <sup>3</sup> ) 1000 (1) (1) 15 minutes average value (IE)

**8.2 Exposure controls**

**Personal protection equipment**

**Eye/face protection**

With demand: protective glasses

**Hand protection**

Gloves (oil-resistant)

Recommendation: protective glove (referred to EN374).

**Respiratory protection**

Respiratory protection must be worn whenever the WEL levels have been exceeded

The following applies to propane in general: If the concentration is exceeded, closed-circuit breathing apparatuses must be used

Use filter apparatus type AX, identification colour brown according to EN 371

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**Physical state**

Aerosol

**Colour**

bräunlich, klar

**Odour**

pleasant

**Safety relevant basis data**

	Value	Method	Source, Remark
Odour threshold:	not determined		
Melting point/freezing point	not determined		
Boiling point or initial boiling point and boiling range	-42 °C pressure 1013 mbar		(Propan)
flammability	not determined		
Lower and upper explosion limit	Upper explosion limit 10.9 Vol-%		(Propan)
Lower and upper explosion limit	Lower explosion limit approx. 1.5 Vol-%		(Propan)
Flash point	approx. -104 °C		(Propan)
Auto-ignition temperature	not determined		
Decomposition temperature	not determined		
pH	not determined		
Viscosity	kinematic approx. 5 mm <sup>2</sup> /s (20°C)		information concerns to liquid phase



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

	Value	Method	Source, Remark
Solubility(ies)	Water solubility		Immiscible
Partition coefficient n-octanol/water (log value)	not determined		
Vapour pressure	not determined		
Density and/or relative density	approx. 0.84 g/cm <sup>3</sup> (20°C) pressure 1013 mbar		information concerns to liquid phase
Relative vapour density	not determined		
particle characteristics	not determined		

**9.2 Other information**

No data available

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No data available

**10.2 Chemical stability**

No data available

**10.3 Possibility of hazardous reactions**

No data available

**10.4 Conditions to avoid**

Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50°C/122°F.

**10.5 Incompatible materials**

Oxidising agent, strong

**10.6 Hazardous decomposition products**

Carbon monoxide  
Carbon dioxide

**Additional information**

Product is stable under normal storage conditions

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

**Animal data**

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	> 2000 mg/kg Species Rat		Data apply to the main component.
Acute dermal toxicity	not determined		
Acute inhalation toxicity	not determined		



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

**Skin corrosion/irritation**

not determined

**Serious eye damage/irritation**

**Animal data**

Result / Evaluation	Method	Source, Remark
---------------------	--------	----------------

slightly irritant		
-------------------	--	--

**Sensitisation to the respiratory tract**

not determined

**Skin sensitisation**

**Animal data**

Result / Evaluation	Dose / Concentration	Method	Source, Remark
---------------------	----------------------	--------	----------------

not sensitising.			
------------------	--	--	--

**Germ cell mutagenicity**

not determined

**Carcinogenicity**

not determined

**Reproductive toxicity**

not determined

**STOT-single exposure**

not determined

**STOT-repeated exposure**

not determined

**Aspiration hazard**

not determined

**11.2 Information on other hazards**

No data available

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity**

	Effective dose	Method, Evaluation	Source, Remark
Acute (short-term) fish toxicity	not determined		
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	not determined		
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	not determined		
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	not determined		



ES WIRKT.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Feinmechanik-Öl Ustanol-Spray

Print date 23.02.2023
Revision date 23.02.2023
Version 8.0 (en)
replaces version of 12.05.2021 (7.8)

12.2 Persistence and degradability

Table with 4 columns: Value, Method, Source, Remark. Row: Biodegradation, Moderately/partially biodegradable.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Table with 2 columns: Waste code product, Waste name. Row: 130205 \*, mineral-based non-chlorinated engine, gear and lubricating oils

Appropriate disposal / Package

Non-contaminated packages may be recycled. Recycle sales packaging via DSD (Duales System Deutschland).

SECTION 14: Transport information

Table with 4 columns: Land transport (ADR/RID), Sea transport (IMDG), Air transport (ICAO-TI / IATA-DGR). Rows: 14.1 UN number or ID number, 14.2 UN proper shipping name, 14.3 Transport hazard class(es), 14.4 Packing group, 14.5 Environmental hazards

14.6 Special precautions for user

No data available

14.7 Maritime transport in bulk according to IMO instruments

No data available

Land transport (ADR/RID)

Table with 2 columns: UN number or ID number, UN proper shipping name, Transport hazard class(es). Row: UN 1950, AEROSOLS, 2.1



**ES WIRKT.**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

---

Hazard label(s)	2.1
Classification code	5F
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	1 L
Special provisions	190, 327, 344, 625
Tunnel restriction code	D

**Remark**

RID: class 23  
Including 1.000 ml LQ max 1L

**Sea transport (IMDG)**

UN number or ID number	UN 1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	1 L
Marine pollutant	No
EmS	F-D, S-U

**Remark**

UN 1950 Aerosols (max1L) IMDG class 2, Code- see SP63, EmS: F-D, S-U ; packaging instructions: P003 - LP02; packaging order: PP17-PP87-L2.

**Air transport (ICAO-TI / IATA-DGR)**

UN number or ID number	UN 1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Packing group	-
Environmental hazards	No

---

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

No data available

**15.2 Chemical Safety Assessment**

For this substance a chemical safety assessment is not required.



**ES WIRKT.**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**Feinmechanik-Öl Ustanol-Spray**

Print date 23.02.2023  
Revision date 23.02.2023  
Version 8.0 (en)  
replaces version of 12.05.2021 (7.8)

---

**SECTION 16: Other information**

**Additional information**

National and local regulations concerning chemicals shall be observed.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

**Relevant H- and EUH-phrases (Number and full text)**

H220 Extremely flammable gas.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Indication of changes**

\* Data changed compared with the previous version