

TECHNICAL DATA SHEET

QH PRESSMAX™ VE 2660

VANISHING STAMPING OIL

QH PRESSMAX™ VE 2660 is based on high purity solvent with low aromatic content. The additives are selected to provide high lubricity in combination with low residue after evaporation.

QH PRESSMAX™ VE 2660 is free from Chlorine, Sulphur, Phosphorous and heavy metals (Zinc)

Applications

QH PRESSMAX™ VE 2660 is an evaporative product for stamping and drawing of thin non-ferrous and ferrous materials.

The product does not leave a residual film or react with paint.

Degreasing of parts before assembly or welding is not necessary.

QH PRESSMAX™ VE 2660 is mainly used for non ferrous materials.

Recommendation For Use

QH PRESSMAX™ VE 2660 is used neat as supplied.

Benefits

- Reduced cost - higher production rates due to strong lubricity
- Reduced cost - easy to be washed off with standard cleaners
- Satisfied staff - good EHS profile, reduced smell.
- Satisfied staff - light color for good monitoring of the operation

Health, Safety And Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

Typical Physical Properties

PROPERTY	TYPICAL VALUE	UNIT
Colour	pale yellow	
Specific Gravity @ 20°C	765	ASTM D 4052, kg/m ³
Kinematic Viscosity @ 40°C	1,3	ASTM D 7042, mm ² /s
Flash Point	66	ASTM D 93, °C
Pour Point	-21	ASTM D 97, °C
Copper Corrosion	1a	ASTM D 130

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 73000201

