

DM542EU/ DM442/ EM542S

Comparison



Leadshine

Comparison of Digital Drivers

DM542EU/ DM442/ EM542S



DM542EU



DM442



EM542S

Leadshine has a wide product range with over 10 million drivers in the market in different price ranges and performances. Below is a comparison of stepper motor drivers for output current of up to 4.2 Ampere.

	DM542EU	DM442	EM542S				
Auto-tuning	✓	✓	✓				
Anti-resonance	✓	✓	✓				
Extra-low motor noise	✓	✓	✓				
Idle-current reduction	✓	✓	✓				
Protection for over-voltage/ over-current	✓	✓	✓				
Optical isolated inputs	✓	✓	✓				
Input PUL/ DIR	✓	✓	✓				
CW/ CCW mode	X	✓	✓				
RS232 programming	X	✓	✓				
Fault & Brake Output	X	X	✓				
Self-test via DIP switch	X	X	✓				
Current setting via software (steps 0.1 A)	X	✓	✓				
Current setting via DIP switches (steps)	8	8	8				
Steps/ revolution via DIP switches	400 - 25,600	400 - 25,600	200 - 25,600				
Selectable micro-step resolutions via DIP switches	16	16	16				
Steps/ revolution via software (increase by 200)	N	200 - 102,400	200 - 51,200				
Voltage tolerance of inputs (High Level)	3.3 - 5.0 V (TTL)	3.3 - 5.0 V (TTL)	3.3 - 5.0 V (TTL)/ 12 - 24 V				
Dimensions [mm]	118 x 75.5 x 25.5	116 x 69.2 x 26.5	118 x 75.5 x 25.5				
Connectors	WANJIE: WJ2EDGK, 5.0 mm pitch, 2-pin WANJIE: WJ2EDGK, 5.0 mm pitch, 4-pin WANJIE: WJ2EDGK, 5.0 mm pitch, 6-pin	ANYTEK: TJ, 3.81 mm pitch, 2-pin ANYTEK: TJ, 3.81 mm pitch, 4-pin ANYTEK: TJ, 3.81 mm pitch, 6-pin	ANYTEK: TJ, 3.81 mm pitch, 3-pin ANYTEK: TJ, 3.81 mm pitch, 6-pin ANYTEK: TJ, 5.0 mm pitch, 2-pin ANYTEK: TJ, 5.0 mm pitch, 4-pin				
Weight	227 g	200 g	250 g				
	Min	Max	Min	Max	Min	Max	Units
Output current via DIPs	1.0	4.2	1.46	4.2	1.0	4.2	A
Output current via SW			0.5	4.2	0.5	4.2	A
Supply voltage	20	50	20	40	20	50	VDC
Logical signal current	7	16	7	16	7	16	mA
Pulse input frequency	0	200	0	200	0	200	kHz
Minimal pulse width	2.5		2.5		2.5		μs
Minimal direction timing	5.0		5.0		5.0		μs
Insulation resistance	500		500		500		MΩ